


POS.	CODE	N° PZ.	DENOMINATION	MATERIAL
7	20/851	1	Ø3/8" BARB WITH SHUT-OFF BALL VALVE UL LISTED	VARIOUS
6	23/10/101	1	3000 PSI TANK GAUGE - 1/4" NPTF-LH - UL LISTED	VARIOUS
5	23/10/97	1	60 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
4	A008	1	O-RING SEAL FOR N2 TANK FITTING	EPDM PEROXIDE 70SH
3	20/10/77	1	CGA-V1 CONNECTION N°580 NUT	BRASS
2	24/510/18	1	N2 TANK FITTING - 1/4" NPTF-LH	BRASS
1	24/504P	1	PRESSURE REGULATOR BODY KIT - 60 PSI - 1/4" NPTF	VARIOUS

FILE: 24PLN_H1L1U10	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW		
ARCHIVE: //			
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	○ IMPORTANT QUOTES	ITALIAN MANUFACTURERS SINCE 1948
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	① INDEX OF CHANGE	
MATERIAL: VARIOUS			
RULES:			



DIS.N°: 24PLN/H1L1U10 - PRESSURE REGULATOR

GROUP

- UL N2 PRIMARY REGULATOR - 60 PSI - INLET CGA-V1 N°580

- 60 PSI AND 3000 PSI GAUGES - OUTLET Ø3/8" BARB WITH BALL VALVE

Rev.	DATE	DESCRIPTION	DIS.	DEL.	RAW PIECE Kg :
0	02-02-2021	EMISSION	BR	TD	FINISHED PIECE Kg : 0.979
FIRST ISSUE: 01-02-2021					MOLD DESIGN:
NOTE:					FORMAT: A3 PAPER: 3

Primary regulator Model: 24PLN
Inlet pressure Max: 2900 psi
Fluid: Nitrogen

Compressed gas regulator
SA44354