




7	20/846	1	Ø5/16" BARB WITH SHUT-OFF BALL VALVE UL LISTED	VARIOUS
6	24/510/13	1	PLUG 1/4" NPTF-LH	BRASS
5	23/10/97	1	60 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
4	24/510/4	1	FLAT SEAL FOR CO2 TANK FITTING	LOW DENSITY POLYTHENE
3	20/10/79	1	CGA-V1 CONNECTION N°320 NUT	BRASS
2	24/510/3	1	CO2 TANK FITTING - 1/4" NPTF-LH	BRASS
1	24/504P	1	PRESSURE REGULATOR BODY KIT - 60 PSI - 1/4" NPTF	VARIOUS
POS.	CODE	N° PZ.	DENOMINATION	MATERIAL

FILE: 24PL_H0L1U2	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW		
ARCHIVE: //			
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	 IMPORTANT QUOTES	ITALIAN MANUFACTURERS SINCE 1948
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	 INDEX OF CHANGE	
MATERIAL: VARIOUS			



RULES: DIS.N°: 24PL/H0L1U2 - PRESSURE REGULATOR GROUP

- UL CO2 PRIMARY REGULATOR - 60 PSI - INLET CGA-V1 N°320
 - 60 PSI GAUGE - OUTLET Ø5/16" BARB WITH BALL VALVE

Rev.	DATE	DESCRIPTION	DIS.	DEL.	RAW PIECE lb :
0	26-06-2020	EMISSION	BR	TD	FINISHED PIECE lb : 1,89

FIRST ISSUE: 16-10-2019 MOLD DESIGN: FORMAT: A3 PAPER: 3

NOTE:

Primary regulator Model: 24PL
 Inlet pressure Max: 2900 psi
 Fluid: Carbon dioxide

Compressed gas regulator
 SA44354