




POS.	CODE	N° PZ.	DENOMINATION	MATERIAL
7	20/851	1	Ø3/8" BARB WITH SHUT-OFF BALL VALVE UL LISTED	VARIOUS
6	23/10/101	1	3000 PSI TANK GAUGE - 1/4" NPTF-LH - UL LISTED	VARIOUS
5	23/10/97	1	60 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
4	24/510/4	1	FLAT SEAL FOR CO2 TANK FITTING	LOW DENSITY POLYTHENE
3	20/10/79	1	CGA-V1 CONNECTION N°320 NUT	BRASS
2	24/510/3	1	CO2 TANK FITTING - 1/4" NPTF-LH	BRASS
1	24/504P	1	PRESSURE REGULATOR BODY KIT - 60 PSI - 1/4" NPTF	VARIOUS

FILE: 24PL_H2L1U10	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW		
ARCHIVE: //			
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	 IMPORTANT QUOTES	ITALIAN MANUFACTURERS SINCE 1948
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	 INDEX OF CHANGE	
MATERIAL: VARIOUS			
RULES:			

DIS.N°: 24PL/H2L1U10 - PRESSURE REGULATOR

GROUP

- UL CO2 PRIMARY REGULATOR - 60 PSI - INLET CGA-V1 N°320

- 60 PSI AND 3000 PSI GAUGES - OUTLET Ø3/8" BARB WITH BALL VALVE

Rev.	DATE	DESCRIPTION	DIS.	DEL.	RAW PIECE Kg :
0	02-02-2021	EMISSION	BR	TD	FINISHED PIECE Kg : 0.956
FIRST ISSUE: 02-05-2019					MOLD DESIGN:

NOTE: FORMAT: A3 PAPER: 3

TOF
TOF SRL

UL LISTED
Compressed gas regulator
SA44354

Primary regulator Model: 24PL
Inlet pressure Max: 2900 psi
Fluid: Carbon dioxide