




| | | | | |
|------|-----------|--------|--|-----------------------|
| 7 | 20/846 | 1 | Ø5/16" BARB WITH SHUT-OFF BALL VALVE UL LISTED | VARIOUS |
| 6 | 23/10/101 | 1 | 3000 PSI TANK GAUGE - 1/4" NPTF-LH - UL LISTED | VARIOUS |
| 5 | 23/10/97 | 1 | 60 PSI GAUGE - 1/4" NPTF - UL LISTED | VARIOUS |
| 4 | 24/510/4 | 1 | FLAT SEAL FOR CO2 TANK FITTING | LOW DENSITY POLYTHENE |
| 3 | 20/10/79 | 1 | CGA-V1 CONNECTION N°320 NUT | BRASS |
| 2 | 24/510/3 | 1 | CO2 TANK FITTING - 1/4" NPTF-LH | BRASS |
| 1 | 24/504P | 1 | PRESSURE REGULATOR BODY KIT - 60 PSI - 1/4" NPTF | VARIOUS |
| POS. | CODE | N° PZ. | DENOMINATION | MATERIAL |

| | | | |
|-------------------|--|--|---|
| FILE: 24PL_H2L1U2 | PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW | |  |
| ARCHIVE: // | | | |
| DEP.: MON-B | TOLLERANCES UNI EN ISO 22768-F |  IMPORTANT QUOTES | ITALIAN MANUFACTURERS SINCE 1948 |
| SCALE: 1:1 | UNLESS WHERE DIFFERENTLY INDICATED |  INDEX OF CHANGE | |
| MATERIAL: VARIOUS | | | |
| RULES: | | | |

DIS.N°: 24PL/H2L1U2 - PRESSURE REGULATOR



GROUP

- UL CO2 PRIMARY REGULATOR - 60 PSI - INLET CGA-V1 N°320

- 60 PSI AND 3000 PSI GAUGES - OUTLET Ø5/16" BARB WITH BALL VALVE

| Rev. | DATE | DESCRIPTION | DIS. | DEL. | RAW PIECE lb : |
|-------------------------|------------|-------------|------|------|--------------------------|
| 0 | 18-10-2018 | EMISSION | BR | TD | FINISHED PIECE lb : 2,10 |
| FIRST ISSUE: 21-05-2018 | | | | | MOLD DESIGN: |

NOTE: FORMAT: A3 PAPER: 3

Primary regulator Model: 24PL
Inlet pressure Max: 2900 psi
Fluid: Carbon dioxide

Compressed gas regulator
SA44354