



POS.	CODE	N° PZ.	DENOMINATION	MATERIAL
7	20/851	1	Ø3/8" BARB WITH SHUT-OFF BALL VALVE UL LISTED	VARIOUS
6	23/10/101	1	3000 PSI TANK GAUGE - 1/4" NPTF-LH - UL LISTED	VARIOUS
5	23/10/98	1	115 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
4	24/510/4	1	FLAT SEAL FOR CO2 TANK FITTING	LOW DENSITY POLYTHENE
3	20/10/79	1	CGA-V1 CONNECTION N°320 NUT	BRASS
2	24/510/3	1	CO2 TANK FITTING - 1/4" NPTF-LH	BRASS
1	24/507P	1	PRESSURE REGULATOR BODY KIT - 100 PSI - 1/4" NPTF	VARIOUS

FILE: 24PL_H2L2U10	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW		
ARCHIVE: //			
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	○ IMPORTANT QUOTES	ITALIAN MANUFACTURERS SINCE 1948
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	① INDEX OF CHANGE	
MATERIAL: VARIOUS			
RULES:			

DIS.N°: 24PL/H2L2U10			GROUP		
- PRESSURE REGULATOR					
- UL CO2 PRIMARY REGULATOR - 100 PSI - INLET CGA-V1 N°320					
- 115 PSI AND 3000 PSI GAUGES - OUTLET Ø3/8" BARB WITH BALL VALVE					
Rev.	DATE	DESCRIPTION	DIS.	DEL.	RAW PIECE Kg :
0	02-02-2021	EMISSION	BR	TD	FINISHED PIECE Kg : 0.956
FIRST ISSUE: 20-01-2021					MOLD DESIGN:
NOTE:					FORMAT: A3 PAPER: 3

Primary regulator Model: 24PL
Inlet pressure Max: 2900 psi
Fluid: Carbon dioxide

Compressed gas regulator
SA44354