


| POS. | CODE | N° PZ. | DENOMINATION | MATERIAL |
|------|-----------|--------|---|-----------------------|
| 7 | 20/851 | 1 | Ø3/8" BARB WITH SHUT-OFF BALL VALVE UL LISTED | VARIOUS |
| 6 | 23/10/101 | 1 | 3000 PSI TANK GAUGE - 1/4" NPTF-LH - UL LISTED | VARIOUS |
| 5 | 23/10/99 | 1 | 160 PSI GAUGE - 1/4" NPTF - UL LISTED | VARIOUS |
| 4 | 24/510/4 | 1 | FLAT SEAL FOR CO2 TANK FITTING | LOW DENSITY POLYTHENE |
| 3 | 20/10/79 | 1 | CGA-V1 CONNECTION N°320 NUT | BRASS |
| 2 | 24/510/3 | 1 | CO2 TANK FITTING - 1/4" NPTF-LH | BRASS |
| 1 | 24/511P | 1 | PRESSURE REGULATOR BODY KIT - 160 PSI - 1/4" NPTF | VARIOUS |

| | | | |
|--------------------|--|--------------------|---|
| FILE: 24PL_H2L3U10 | PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW | |  |
| ARCHIVE: // | | | |
| DEP.: MON-B | TOLLERANCES UNI EN ISO 22768-F | ○ IMPORTANT QUOTES | ITALIAN MANUFACTURERS SINCE 1948 |
| SCALE: 1:1 | UNLESS WHERE DIFFERENTLY INDICATED | ① INDEX OF CHANGE | |
| MATERIAL: VARIOUS | | | |
| RULES: | | | |

| | | | |
|---|--|-------|--|
| DIS.N°: 24PL/H2L3U10 | | GROUP | |
| - PRESSURE REGULATOR | | | |
| - UL CO2 PRIMARY REGULATOR - 160 PSI - INLET CGA-V1 N°320 | | | |
| - 160 PSI AND 3000 PSI GAUGES - OUTLET Ø3/8" BARB WITH BALL VALVE | | | |

| Rev. | DATE | DESCRIPTION | DIS. | DEL. | RAW PIECE Kg : |
|-------------------------|------------|-------------|------|------|---------------------------|
| 0 | 02-02-2021 | EMISSION | BR | TD | FINISHED PIECE Kg : 0.959 |
| FIRST ISSUE: 20-01-2021 | | | | | MOLD DESIGN: |
| NOTE: | | | | | FORMAT: A3 PAPER: 3 |



TOF SRL

Primary regulator Model: 24PL
Inlet pressure Max: 2900 psi
Fluid: Carbon dioxide



Compressed gas regulator
SA44354