




POS.	CODE	N° PZ.	DENOMINATION	MATERIAL
6	23/621-CN1	2	MOUNTING BRACKET KIT	VARIOUS
5	20/846	2	Ø5/16" BARB WITH SHUT-OFF BALL VALVE UL LISTED	VARIOUS
4	20/846/1	2	FITTING BARB Ø5/16"	BRASS
3	23/10/97	2	60 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
2	24/510/20	1	CONNECTION FITTING 1/4" NPT - L=40	BRASS
1	24/500P-IM	2	SECONDARY PRESSURE REGULATOR BODY KIT - 1/4" NPTF	VARIOUS

FILE: 24SLD_L1C1U2F	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW			 ITALIAN MANUFACTURERS SINCE 1948	
ARCHIVE: //					
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	○ IMPORTANT QUOTES			
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	Ⓜ INDEX OF CHANGE			
MATERIAL: VARIOUS					
RULES:					
DIS.N°: 24SLD/L1C1U2F		- PRESSURE REGULATOR		GROUP	
- UL SECONDARY REGULATOR 2 BODIES - SIDE CONNECTIONS BARB Ø5/16"					
- PRESSURE GAUGES 60 PSI - OUTLET Ø5/16" BARB WITH BALL VALVE - MOUNTING BRACKET					
Rev.	DATE	DESCRIPTION	DIS.	DEL.	RAW PIECE Kg :
0	25-10-2018	EMISSION	BR	TD	FINISHED PIECE Kg : 1.485
FIRST ISSUE: 25-10-2018				MOLD DESIGN:	
NOTE:				FORMAT: A2	PAPER: 3

 Primary regulator Model: 24SLD
 Inlet pressure Max: 200 psi
 Fluid: Carbon dioxide, Nitrogen
 Compressed gas regulator
 SA44354