




POS.	CODE	N° PZ.	DENOMINATION	MATERIAL
8	24/510/21	1	PLUG 1/4" FLARE	BRASS
7	80/586	1	PLUG GASKET	RUBBER
6	23/621-CN1	2	MOUNTING BRACKET KIT	VARIOUS
5	24/510/17	2	1/4" FLARE WITH CHECK	VARIOUS
4	20/828/1	2	1/4" FLARE FITTING	BRASS
3	23/10/98	2	115 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
2	24/510/20	1	CONNECTION FITTING 1/4" NPT - L=40	BRASS
1	24/500P-IM	2	SECONDARY PRESSURE REGULATOR BODY KIT - 1/4" NPTF	VARIOUS

FILE: 24SLD_L2C2U8SF	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW		 ITALIAN MANUFACTURERS SINCE 1948
ARCHIVE: //			
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	○ IMPORTANT QUOTES	
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	Ⓜ INDEX OF CHANGE	
MATERIAL: VARIOUS			
RULES:			
DIS.N°: 24SLD/L2C2U8SF		GROUP	
- UL SECONDARY REGULATOR 2 BODIES - SIDE CONNECTIONS 1/4" FLARE - PLUG ON LEFT			
- PRESSURE GAUGES 115 PSI - OUTLET 1/4" FLARE WITH CHECK - MOUNTING BRACKETS			
Rev.	DATE	DESCRIPTION	DIS. DEL. RAW PIECE lb :
0	26-06-2020	EMISSION	BR TD FINISHED PIECE lb : 3,02
FIRST ISSUE: 16-10-2019			MOLD DESIGN:
NOTE:			FORMAT: A2 PAPER: 3



  
 Primary regulator Model: 24SLD  
 Inlet pressure Max: 200 psi  
 Fluid: Carbon dioxide, Nitrogen  
 Compressed gas regulator  
 SA44354