




POS.	CODE	N° PZ.	DENOMINATION	MATERIAL
5	23/621-CN1	1	MOUNTING BRACKET KIT	VARIOUS
4	20/846	1	Ø5/16" BARB WITH SHUT-OFF BALL VALVE UL LISTED	VARIOUS
3	20/846/1	2	FITTING BARB Ø5/16"	BRASS
2	23/10/97	1	60 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
1	24/500P-IM	1	SECONDARY PRESSURE REGULATOR BODY KIT - 1/4" NPTF	VARIOUS

FILE: 24SL_L1C1U2F	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW		
ARCHIVE: //			
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	 IMPORTANT QUOTES	ITALIAN MANUFACTURERS SINCE 1948
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	 INDEX OF CHANGE	
MATERIAL: VARIOUS			
RULES:			

DIS.N°: 24SL/L1C1U2F - PRESSURE REGULATOR GROUP

- UL SECONDARY REGULATOR - SIDE CONNECTIONS BARB Ø5/16"

- PRESSURE GAUGE 60 PSI - OUTLET Ø5/16" BARB WITH BALL VALVE - MOUNTING BRACKET

Rev.	DATE	DESCRIPTION	DIS.	DEL.	RAW PIECE lb :
0	25-10-2018	EMISSION	BR	TD	FINISHED PIECE lb : 1,64
FIRST ISSUE: 25-10-2018					MOLD DESIGN:
NOTE:					FORMAT: A3 PAPER: 4

TOF 

Primary regulator Model: 24SL
 Inlet pressure Max: 200 psi
 Fluid: Carbon dioxide, Nitrogen

Compressed gas regulator
 SA44354