





POS.	CODE	N° PZ.	DENOMINATION	MATERIAL
7	23/621-CN1	1	MOUNTING BRACKET KIT	VARIOUS
6	24/510/21	1	PLUG 1/4" FLARE	BRASS
5	80/586	1	PLUG GASKET	RUBBER
4	20/845	1	1/4" FLARE W/CHECK WITH SHUT-OFF BALL VALVE UL LISTED	VARIOUS
3	20/828/1	2	1/4" FLARE FITTING	BRASS
2	23/10/98	1	115 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
1	24/500P-IM	1	SECONDARY PRESSURE REGULATOR BODY KIT - 1/4" NPTF	VARIOUS

FILE: 24SL_L2C2U5SF	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW		
ARCHIVE: //			
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	 IMPORTANT QUOTES	ITALIAN MANUFACTURERS SINCE 1948
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	 INDEX OF CHANGE	
MATERIAL: VARIOUS			
RULES:			

DIS.N°: 24SL/L2C2U5SF			GROUP		
- PRESSURE REGULATOR					
- UL SECONDARY REGULATOR - SIDE CONNECTIONS 1/4" FLARE - PLUG ON LEFT					
- PRES. GAUGE 115 PSI - OUTLET 1/4" FLARE W/CHECK WITH BALL VALVE - MOUNT. BRACKET					
Rev.	DATE	DESCRIPTION	DIS.	DEL.	RAW PIECE lb :
0	26-06-2020	EMISSION	BR	TD	FINISHED PIECE lb : 1,71
FIRST ISSUE: 16-10-2019					MOLD DESIGN:
NOTE:					FORMAT: A3 PAPER: 3

**TOF** 

Primary regulator Model: 24SL  
 Inlet pressure Max: 200 psi  
 Fluid: Carbon dioxide, Nitrogen

Compressed gas regulator  
 SA44354