






POS.	CODE	N° PZ.	DENOMINATION	MATERIAL
8	80/585	3	1/4" FLARE CONICAL GASKET	PLASTIC
7	23/621-CN1	1	MOUNTING BRACKET KIT	VARIOUS
6	24/510/21	1	PLUG 1/4" FLARE	BRASS
5	80/586	1	PLUG GASKET	RUBBER
4	24/510/17	1	1/4" FLARE WITH CHECK	VARIOUS
3	20/828/1	2	1/4" FLARE FITTING	BRASS
2	23/10/98	1	115 PSI GAUGE - 1/4" NPTF - UL LISTED	VARIOUS
1	24/500P-IM	1	SECONDARY PRESSURE REGULATOR BODY KIT - 1/4" NPTF	VARIOUS

FILE: 24SL_L2C2U8SF	PROPRIETARY DESIGN FOR ALL PURPOSES OF LAW		
ARCHIVE: //			
DEP.: MON-B	TOLLERANCES UNI EN ISO 22768-F	 IMPORTANT QUOTES	ITALIAN MANUFACTURERS SINCE 1948
SCALE: 1:1	UNLESS WHERE DIFFERENTLY INDICATED	 INDEX OF CHANGE	
MATERIAL: VARIOUS			
RULES:			

DIS.N°: 24SL/L2C2U8SF			GROUP		
- PRESSURE REDUCER					
- UL SECONDARY REGULATOR - SIDE CONNECTIONS 1/4" FLARE - PLUG ON LEFT					
- PRESSURE GAUGE 115 PSI - OUTLET 1/4" FLARE W/CHECK - MOUNTING BRACKET					
Rev.	DATE	DESCRIPTION	DIS.	DEL.	RAW PIECE Kg :
0	25-10-2018	EMISSION	BR	TD	FINISHED PIECE Kg : 0.697
FIRST ISSUE: 25-10-2018					MOLD DESIGN:
NOTE:					FORMAT: A3 PAPER: 3

 **TOF SRL**

 **LISTED**

Primary regulator Model: 24SL  
Inlet pressure Max: 200 psi  
Fluid: Carbon dioxide, Nitrogen

Compressed gas regulator  
SA44354